

Door entry

Components and accessories



Posts

The mounting of an entrance panel on a post is often required for a variety of applications e.g. for buildings where a wall mounting panel is not suitable or for entrances to car parks.

The posts are manufactured from polished stainless steel and are designed to accommodate surface vandal resistant panels of all sizes. The posts have a stainless steel pedestal welded to the base with fixing holes pre-drilled.

All posts are supplied with surface vandal resistant panels pre-fitted and cable entries pre-drilled. Select the appropriate post and order together with the chosen panel design. The panels can be multi-button, video, digital or combined with proximity or coded keypad.

Please contact the Sales Department for guidance on suitable panel designs.

| Code | Description | Heightmm |
|------|-----------------------------------|-----------|
| CHP1 | Car height post | 1200 |
| PHP1 | Pedestrian height post | 1600 |
| DHP1 | Dual height post - Pedestrian/Car | 1600/1200 |
| DHP2 | Dual height post - HGV/Car | 2000/1200 |

Post width: 80mm

Model TS2000-BST

12V quartz reserve time clock with auto British Summer Time settings.

The TS2000-BST time clock has the facility of automatically adjusting to European/British time settings. Once the user has programmed the date the clock will automatically adjust each spring and autumn. This digital timer is purpose made for access control systems as it operates from a supply voltage of 12V AC/DC. The clock is designed for wall mounting and its main features are;

- Automatic European Time adjustment
- 12V AC/DC operating voltage
- LCD display
- Quartz crystal timing with reserve
- Daily and weekly programs
- 7 day programming
- 8 on/off periods
- 15 repeat options: day, week, weekend, odd weekdays etc.
- Manual override
- Switching capacity 10A/30V DC

Dimensions (mm): H 98 x W 66 x D 40



Speech unit model 61

This compact unit is fitted to the entrance panel on all our current door entry systems (except as indicated below). The unit provides two-way speech and has an individual volume control for both microphone and speaker. This universal product can be powered from either 12V AC or 12V DC depending on the model of telephone used.

Dimensions (mm): H 97 x W 58 x D 24

Speech unit model 51

This unit is generally required as a replacement unit for older systems or for SPA panels above 10 buttons. The unit provides two-way speech and has an individual volume control for both microphone and speaker. This universal product can be powered from either 12V AC or 12V DC depending on the model of telephone used.

Dimensions (mm): H 136 x W 81 x D 30



Extension sounders

These units extend the call tone of a door entry telephone to other areas of the premises to improve audibility. The unit is fabricated in white ABS plastic and can be wall mounted in a convenient indoor location. Available models;
Model RT27 for extensions to the standard 801 telephones
Model BS-RT for extensions to the bellissimo telephones
Model SG1 Sound generator with eight selectable tones

Dimensions (mm): H 120 x W 90 x D 38

Flashing beacon model FB31

This unit gives an effective visual indication of a call at the door entry telephone. This unit is ideal for the 'hard of hearing' or areas with a high level of background noise. The beacon includes a timer circuit that can be set for between 4 and 40 seconds. (A model 212 power supply may be required).

Model FB31 - for audio systems
Model BS-FB - for video systems

Dimensions: H 113mm x W 80mm x D 60mm



Fire Switch (Flush) model FS1-F

Flush mounting stainless steel Fireman's Drop-Key Switch with security fixings and permanently engraved with FIRE CONTROL.

Dimensions (mm): Plate H 150 x W 150
Box H 107 x W 107 x D 65

Fire Switch (Surface) model FS1-S

Surface mounting red powder coated Fireman's Drop-Key Switch with stainless steel plate and security fixings, permanently engraved with FIRE CONTROL.

Dimensions (mm): H 115 x W 115 x D 72



Lock Releases

The standard lock releases are designed to operate with night latch locks on timber framed doors. Each release is fabricated from a variety of materials;

- Main mechanism - plated zinc
- Faceplate - epoxy painted steel
- Latch - chrome-plated mazac zinc alloy
- Side cover - stainless steel



| Model | 12V AC | 12V DC | Surface | Mortice | Fail-secure | Fail-Safe | Continuously Rated | Monitor Switch | Delayed Action | Heavy Duty |
|---------|--------|--------|---------|---------|-------------|-----------|--------------------|----------------|----------------|------------|
| 203 | ■ | ■ | ■ | | ■ | | | | | |
| 204 | ■ | ■ | | ■ | ■ | | | | | |
| 205 | ■ | ■ | ■ | ■ | ■ | | | | ■ | |
| 206 | | ■ | ■ | ■ | | ■ | ■ | | | |
| 209 | | ■ | ■ | ■ | ■ | | ■ | | | |
| 210 | ■ | ■ | ■ | ■ | ■ | | | | | |
| 2208 | ■ | ■ | | ■ | ■ | | | | | ■ |
| 2208 M | ■ | ■ | | ■ | ■ | | | ■ | | ■ |
| 2208 F | | ■ | | ■ | | ■ | ■ | | | ■ |
| 2208 FM | | ■ | | ■ | | ■ | ■ | ■ | | ■ |

Exit Switch (flush mounting) model 5078

An alternative style exit switch with the panel manufactured in 2.5mm 316 marine grade stainless steel and designed to fit a standard single-gang back-box. The panel is permanently engraved and includes a model B24S vandal resistant push-button designed for heavy use.

Plate Dimensions (mm): H 100 x W 100

Back-box dimensions (mm): H 75 x W 75 x D 5



Exit Switch (miniature surface mounting) model 5080

This slim-line surface fitting exit switch is manufactured in a robust alloy casting and has universal graphic symbols and is perfect for architrave fitting. The switch is rated at 3A with 12V – 24V.

Dimensions (mm): H 83 x W 32 x D 25

Exit Switch model TF-EB

The contactless sensor is embedded in a stainless steel face plate and is illuminated with red and green indication lights. The robust, high impact green plastic casing can be flush or surface mounted. The proximity distance to the sensor can be adjusted between 30mm - 120 mm. The unit is for internal use only.

Dimensions (mm): H 85 x W 85 x D 28



Emergency Door Release Button model BG78

A double pole emergency resettable door release push button with a front cover. It operates with 12V DC and includes a buzzer and LED indication.

Dimension (mm): H 85 x W 88 x D 51



Exit switch model GBEB

A stainless steel plate with a large green dome push button. Supplied with a green plastic surface box or can be flush fitted on a single gang box. The option of a stainless steel surface housing is available with the addition of a model GBSS.

Dimension (mm): H 85 x W 85 x D 28

Power supplies

Model 212 (12V AC)

A wall-mounting, double insulated, fused transformer included in basic audio door entry systems up to 10 stations. It has a nominal output of 12V AC @ 1A.

Dimensions (mm): H 140 x W 60 x D 53



Model 225 (12V AC)

A wall mounting, double insulated, fused transformer for use with door entry telephone systems. This supply incorporates a relay for the direct operation of the lock release to overcome possible voltage drop on larger systems. It has a nominal output of 12V AC @ 2 Amps.

Dimensions (mm): H 110 x W 235 x D 80

Model 340C (12V DC)

A wall-mounting fused 12V DC regulated power supply rated at 1.5 Amp for use on DC door entry systems and our Access Control systems. It can also be used for directly powering fail-safe and continuously rated lock releases.

Dimensions (mm): H 140 x W 60 x D 53



Model PS4 (12V DC)

A wall-mounting fused 12V DC regulated power supply rated at 4 Amps for use on video entry systems and for powering high current door release mechanisms.

Dimensions (mm): H 110 x W 235 x D 80